Supermicro Server 5028A-TN4



Highlights

Compact design for network security appliance, high performance NAS, and corporate-WINS/DNS/print/login.

Reduce cost and time spending with our global partner model based on your specific requirements. Let Blue Line take responsibility for delivery on time. Blue Line's ultimate goal is to help our customers get peace of mind by handling all relevant details such as securing the right configuration, software setup, mounting, packaging, labeling etc. Ask for references from your industry.



- Space-efficient mini-tower
- Intel onboard Atom C2758 CPU
- 4 x 3.5" and 2 x 2.5" drive bays
- Quad 1GbE
- · Build-to-order configured to the requirements



- has more than 30 years experience
- delivers reliable IT solutions for demanding environments
- builds compact and high performance solutions
 focuses on long duration, 24/7-operation, and ruggedness
- is ISO 9001:2015-certified
- is known for providing the best assistance and services in all phases.

Specifications

Model Type

Server

Form Factor

Mini tower

Environment

Operating temperature	0°C to 40°C
Non-operating temperature	-20°C to 60°C
Operating humidity	10% to 85% (non-condensing)
Non-operating humidity	10% to 95% (non-condensing)

Processor

Intel® Atom C2758

RAM

Memory capacity	4 x 204-pin DDR3 SO-DIMM slots Supports up to 64GB DDR3 ECC memory
Memory type	1333 / 1600MHz ECC DDR3 SDRAM 72bit, 204pin gold-plated DIMMs
DIMM sizes	2GB / 4GB / 8GB / 16GB
Memory voltage	1.5V / 1.35V

Storage

4 x Hot-swap 3.5" SATA trays 2 x Internal 2.5" HDD bays

Input / Output

Rear	4 x RJ45 gigabit ethernet, 1 x RJ45 dedicated IPMI
	3 x USB 3.0 (2 x rear, 1 x type A)
	1 x Fast UART 16550 serial port
	1 x SATA DOM power connector
	1 x VGA port
Internal	2 x SATA3 (6Gbps) ports, 4 x SATA2 (3Gbps) ports
	1 x TMP 1.2

LINE

Expansion

1 x PCI-E 2.0 x8 slot

Operating System

WHQL RHEL / Ubuntu / SUSE

Power Supply

	250W flex ATX multi-output bronze power supply
AC voltage	100V to 240V / 50 to 60Hz
+5V	max 14Amp / min 0.5Amp
+12V	max 18Amp / min 1Amp (100V to 240V)
-12V	max 0.3Amp
+3.3V	max 12Amp / min 0.3Amp
5VSB	max 2.5Amp

Dimension and Weight

H 240 x W 210 x D 279mm

6.8kg

Accessories Included

4 x SATA, INT, round, ST, 21cm, 30AWG

Accessories Optional

Black teac slim DVD-RW SATA drive, HF, RoHS / REACH, PBF

Slim SATA DVD kit

Big 4pin (male) to big 4pin (female) power extension 15cm, 20AWG, RoHS / REACH

Warranty and After Sales Support

Standard 1 year hardware warranty for barebone

3 year hardware warranty & 1 year cross shipment for complete system CPU / MEM / DISK

Option for 5 year hardware warranty & 1 year cross shipment / 3 year hardware warranty & 3 year cross shipment



BLU

IT for Demanding Environments