## Blue Line Industrial Panel PC-6000





### Highlights

Industrial panel pc with extended temperature operation and large range of I/O.

Reduce cost and time spending with our global partner model based on your specific requirements. Let Blue Line take responsibility for delivery on time. Blue Line's ultimate goal is to help our customers get peace of mind by handling all relevant details such as securing the right configuration, software setup, mounting, packaging, labeling etc. Ask for references from your industry.



- Extended temp -20°C to 55°C
- 10.1" to 21.5" PCAP multi touch display
- Up to full HD resolution 1920 x 1080
- Integrated Intel Core i5
- Fanless operation
- Windows 7 / 8 / 10
- Linux support
- IP65 front panel
- VESA / Panel mount
- Other mounting wall / pipe / swirvel arm / gas arm



- has more than 30 years experience
- delivers reliable IT solutions for demanding environments
- builds compact and high performance solutions
  focuses on long duration, 24/7-operation, and ruggedness
- is ISO 9001:2015-certified
- is known for providing the best assistance and services in all phases.

## Blue Line Industrial Panel PC-6000

## **Specifications**

**Model Type** 

Panel PC

Construction

Aluminum front bezel and SGCC steel chassis

Cooling

**Fanless** 

**Ingress Protection** 

Front IP65 Back IP30

**Environment** 

Operating -20°C to +55°C (operation below 0°C temperature demands a storage device with extended

temperature)

Storage

temperature

-30°C to +70°C

Humidity 10% to 95% RH (non-condensing)

Certification

CE, FCC Class A

Display

1280 x 800, TFT LCD 10.1" LED backlight 16:10, WXGA panel 11.6" 1920 x 1080, TFT LCD LED backlight 16:9, FHD panel 15.6" 1366 x 768, TFT LCD LED backlight 16:9, WXGA panel 18.5" 1366 x 768, TFT LCD LED backlight 16:9, WXGA panel 21.5" 1920 x 1080, TFT LCD LED backlight

panel

Touch

Projected capacitive multi touch panel

16:9, FHD

**Brightness** 

10.1" 350 nits 11.6" 300 nits 15.6" 300 nits

18.5" 300 nits

21.5" 250 nits

**Colors** 

16.2M

**Viewing Angle** 

80/80

85/85

**Processor** 

Intel Core i5-6300U Skylake processor 2.4GHz

**Chipset** 

Integrated SoC

**RAM** 

4GB DDR4 SO-DIMM

Up to 16GB

Storage

10.1", 11.6" 1 x mSATA SSD

15.6", 18.5", 1 x mSATA SSD, 2 x 2.5" SSD / HDD

21.5" (default, outside-accessible)

**Rear Input / Output** 

10.1", 11.6" 2 x RS-232/422/485, 4 x Type-A USB 3.0 /

2.0 porte, 2 x RJ-45 GbE porte, 1 x VGA / 1 x

HDMI

15.6", 18.5", 4 x RS-232/422/485, 4 x Type-A USB 3.0 /

21.5" 2.0 porte, 2 x RJ-45 GbE porte, 1 x VGA / 1 x

HDMI

Option for 4IN / 4OUT Digital I/O

15.6", 18.5",

21.5"

Optional 2 x SMA antenna holes for WiFi function



# Blue Line Industrial Panel PC-6000

#### **Expansion**

1 x mPCle Slot (PClex1 + USB 2.0, full size) 1 x mPCle Slot (PClex1 + USB 2.0, half size)

#### **Operating System**

Windows 7 / 8 / 10

Windows Embedded Standard 7 / 8

Windows 10 IoT Enterprise

Ubuntu Linux

#### **Power Supply**

10.1", 11.6" +12V to +28V DC-in by jack stick (optional 60W AC / DC power adapter kit)

15.6", 18.5", +9V to +36V DC-in by terminal block (optional 12V/5A 60W AC / DC power adapter kit)

#### WIFI modul

3G / 4G modul

15.6", 18.5",  $\,$  12V/5A 60W AC to DC power adapter kit

21.5" with terminal block

10.1", 11.6" 12V/5A 60W AC to DC power adapter kit

with jack

10.1", 11.6" Panel mounting kit

10.1", 11.6" DC-in jack to terminal block

#### **Warranty and After Sales Support**

Standard 1 year (option for 3 years)

#### **Ordering Information**

1247

#### **Power Consumption**

10.1" Max. 23W (w/o I/O cards)
11.6" Max. 24W (w/o I/O cards)
15.6" Max. 30.8W (w/o I/O cards)
18.5" Max. 29W (w/o I/O cards)
21.5" Max. 38.1W (w/o I/O cards)

Max 30.8W (without I/O cards)

#### **Mounting**

Panel mounting VESA 100

#### **Dimension and Weight**

10.1"	H 175 x W 255 x D 46.8mm	2.07kg
11.6"	H 206 x W 306.2 x D 46.9mm	2.45kg
15.6"	H 255 x W 404 x D 56.3mm	4.46kg
18.5"	H 295 x W 470 x D 56.2mm	5.68kg
21.5"	H 332 x W 536 x D 55.5mm	7.01kg

#### **Accessories Included**

15.6", 18.5", Panel mounting kit 21.5"

#### **Accessories Optional**

