Supermicro Workstation 7048A-T





Highlights

Whisper quiet workstation for virtualization and multi tasking.



- Workstation tower
- Option for 4U rack mount kit
- 2 x Intel Xeon E5-2600 v4 Series
- Max 2 x dual & 1 x single slot GPU
- Option for Thunderbolt 2 kit
- · Build-to-order configured to the requirements







- has more than 30 years experience
- delivers reliable IT solutions for demanding environments
- builds compact and high performance solutions
 focuses on long duration, 24/7-operation, and ruggedness
- is ISO 9001:2015-certified
- is known for providing the best assistance and services in all phases.

Supermicro Workstation 7048A-T

Specifications

Model Type

Workstation

Form Factor

Tower (option for 4U rackmount)

Cooling

2 x 2800 RPM fans 1 x 2700 RPM fan

Environment

Operating 10°C to 35°C

temperature

Non-operating -40°C to 70°C

temperature

Operating 8% to 90% (non-condensing)

humidity

Non-operating 5% to 95% (non-condensing)

humidity

Processor

CPU Intel® Xeon E5-2600 v4 / v3 family (up to

160W TPD) dual socket R3

Cores / cache up to 22 cores / up to 55MB cache

System bus QPI up to 9.6GT/s

Chipset

Intel® C612

RAM

Memory 16 x 288pin DDR4 DIMM slots

up to 2TB ECC 3DS LRDIMM, 521GB ECC capacity

RDIMM

2400 / 2133 / 1866 / 1600MHz ECC DDR4 Memory type

SDRAM 72bit

DIMM sizes RDIMM 4GB / 8GB / 16GB / 32GB

LRDIMM 32GB / 64GB 3DS LRDIMM 128GB

Memory

voltage

Error corrects single-bit errors

detection

Storage

8 x Hot-swap 3.5" SAS / SATA drive trays

Input / Output

Rear 2 x RJ45 gigabit, 2 x DOM

> 1 x 7.1 HD audio with optical S/PDIF 6 x USB 3.0 (4 x rear, 2 x header)

5 x USB 2.0 (2 x rear, 2 x header, 1 x type

Internal 10 x SATA3 (6Gbps) ports

1 x TPM 1.2 20pin

Expansion

3 x PCI-E 3.0 x16 slots

2 x PCI-E 3.0 x8 slots

1 x PCI-E 2.0 x4 (in x8) slot

Supports Thunderbolt 2.0 AIC

Operating System

WHQL

RHEL / Ubuntu / SUSE

Power Supply

1200W high-efficiency power supply w/

PMBus

AC input 1000W 100V to 114.9V / 50 to 60Hz / 12

1200W 114.9V to 240V / 50 to 60Hz / 12

to 8 Amp

DC output +3.3V / +5V / +12V / -12V / +5VSB

Max 1000W 20A / 20A / 83A / 0.3A / 3A

Max 1200W 20A / 20A / 99A / 0.3A / 3A

Dimension and Weight

H 452 x W 178 x D 648mm 32.2kg

Accessories Included

2 x CBL, SGPIO, 2x4F to 2x4F, P2.54, round, 40cm, 28AWG

8 x SATA, INT, round, ST, 55cm, 30AWG

1 x PS2 1200W multi output high efficiency power supply

1 x Manual



Supermicro Workstation 7048A-T

Accessories Optional

Mounting rails
Fan 80 x 38mm 4pin PWM
Black hot-swap 3.5" to 2.5" HDD tray

Warranty and After Sales Support

Standard 1 year hardware warranty for barebone

3 year hardware warranty & 1 year cross shipment for complete system CPU / MEM / DISK

Option for 5 year hardware warranty $\&\ 1$ year cross shipment / 3 year hardware warranty $\&\ 3$ year cross shipment