

Supermicro Server 5028D-TN4T



Highlights

Compact design for network security appliance, high performance NAS servers, and small/medium business.

Reduce cost and time spending with our global partner model based on your specific requirements. Let Blue Line take responsibility for delivery on time. Blue Line's ultimate goal is to help our customers get peace of mind by handling all relevant details such as securing the right configuration, software setup, mounting, packaging, labeling etc. Ask for references from your industry.



- Space-efficient mini-tower
- Intel onboard Xeon D-1541 CPU
- 4 x 3.5" & 2 x 2.5" drive bays
- Dual 1GbE & Dual 10GbE
- Build-to-order configured to the requirements



BLUE LINE
IT for Demanding Environments

- has more than 30 years experience
- delivers reliable IT solutions for demanding environments
- builds compact and high performance solutions
- focuses on long duration, 24/7-operation, and ruggedness
- is ISO 9001:2015-certified
- is known for providing the best assistance and services in all phases.

Supermicro Server 5028D-TN4T

Specifications

Model Type

Server

Form Factor

Mini tower

Environment

Operating temperature 0°C to 40°C

Non-operating temperature -20°C to 60°C

Operating humidity 10% to 85% (non-condensing)

Non-operating humidity 10% to 95% (non-condensing)

Processor

Intel Xeon D-1541

FCBGA 1667 supported

CPU TDP supports 45W

System-on-chip

RAM

Memory capacity 4 x DDR4 DIMM sockets
up to 128GB ECC RDIMM
up to 64GB DDR4 ECC/non-ECC UDIMM

Memory type 2400 / 2133 / 1600 / 1333MHz ECC DDR4 SDRAM

DIMM sizes 4GB / 8GB / 16GB / 32GB

Memory voltage 1.2V

Error detection corrects single-bit errors
detects double-bit errors

Storage

4 x Hot-swap 3.5" drive bays

2 x Internal 2.5" drive bays

Input / Output

Rear 2 x RJ45 gigabit, 2 x RJ45 10GBase-T
1 x RJ45 dedicated IPMI
2 x USB 3.0 (rear), 2 x USB 2.0 (front)

Internal 1 x SATA DOM, 1 x VGA
6 x SATA3 (6Gbps) ports
1 x COM, 1 x TMP 2.0

Expansion

1 x PCI-E 3.0 x16 (low profile)

1 x M.2 PCI-E 3.0 x4, Mkey 2242 / 2280

Operating System

WHQL

RHEL / Ubuntu / SUSE

VMware

Power Supply

250W flex ATX multi-output bronze power supply

AC voltage 100V to 240V / 50 to 60Hz

+5V standby max 14Amp / min 0.5Amp

+12V max 18Amp / min 1Amp / 100V to 240V

-12V max 0.3Amp

+3.3V max 12Amp / min 0.3Amp

5VSB max 2.5Amp

Dimension and Weight

H 240 x W 210 x D 279mm 6.8kg

Accessories Included

1 x Air shroud

1 x SATA, INT, round, ST, 29cm, 30AWG

4 x SATA, INT, round, ST, 21cm, 30AWG

1 x CBL, SGPIO, 2x4F to 2x4F, P2.54, ribbon in round tube, 40cm, 28AWG

1 x 1U 250W flex ATX multi-output bronze power supply

Accessories Optional

Black teac slim DVD-RW SATA drive, HF, RoHS / REACH, PBF

Slim SATA DVD kit

Big 4pin (male) to big 4pin (female) power extension 15cm, 20AWG, RoHS / REACH

Warranty and After Sales Support

Standard 1 year hardware warranty for barebone

3 year hardware warranty & 1 year cross shipment for complete system CPU / MEM / DISK

Option for 5 year hardware warranty & 1 year cross shipment / 3 year hardware warranty & 3 year cross shipment



BLUE LINE
IT for Demanding Environments

Blue Line A/S | Kappa 8 | 8382 Hinnerup, Denmark
T +45 8678 5000 | www.blue-line.com