

Supermicro Storage Server 2029P-E1CR24H/L



Highlights

High performance computing, database processing, and enterprise storage server.

Reduce cost and time spending with our global partner model based on your specific requirements. Let Blue Line take responsibility for delivery on time. Blue Line's ultimate goal is to help our customers get peace of mind by handling all relevant details such as securing the right configuration, software setup, mounting, packaging, labeling etc. Ask for references from your industry.



- 2U rack mount chassis
- 2 x Intel 2nd gen. Xeon Scalable
- Broadcom 3108 HW RAID (H)
- Broadcom 3008 HBA (L)
- 24 x Hot-swap 2.5" drive bays and JBOD expansion port
- Build-to-order configured to the requirements



BLUE LINE
IT for Demanding Environments

- has more than 30 years experience
- delivers reliable IT solutions for demanding environments
- builds compact and high performance solutions
- focuses on long duration, 24/7-operation, and ruggedness
- is ISO 9001:2015-certified
- is known for providing the best assistance and services in all phases.

Supermicro Storage Server 2029P-E1CR24H/L

Specifications

Model Type

Storage server

Form Factor

2U rackmount

Cooling

3 x Hot-swap 8cm redundant PWM cooling fans

Environment

Operating temperature 10°C to 35°C

Non-operating temperature -40°C to 60°C

Operating humidity 8% to 90% (non-condensing)

Non-operating humidity 5% to 95% (non-condensing)

Certification

UL / cUL / CB / BSMI / CE / CCC

Processor

CPU 2. gen Intel® Xeon scalable (cascade lake / skylake) dual socket P
3 UPI up to 10.4GT/s
supports CPU TDP 70 to 205W

Cores / cache Up to 22 cores / up to 55MB cache

Chipset

Intel® C622

RAM

Memory capacity 16 x DIMM slots
up to 4TB ECC 3DS DDR4-2933MHz RDIMM / LRDIMM

Memory type 2133 / 2400 / 2666 / 2933MHz ECC DDR4
RDIMM / LRDIMM

Storage

24 x Hot-swap 2.5" SAS3 / SATA3 drive bays

2 x Hot-swap 2.5" SATA3 drive bays (rear)

Option for 2 x onboard NVMe M.2

Input / Output

Rear 2 x RJ45 10GBase-T, 1 x RJ45 dedicated IPMI
1 x VGA

4 x USB 3.0

Internal 1 x fast UART 16550 port

1 x USB type A

Expansion

3 x PCI-E 3.0 x16 slot

4 x PCI-E 3.0 x8 slots

Slot 2 & 3 occupied by controller and JBOD expansion port

Operating System

WHQL

RHEL / Ubuntu / SUSE

Power Supply

1200W redundant power supplies with
PMBus

Total output power 1000W / 1200W

Input 100V to 127V AC / 15 to 12A / 50 to 60Hz
200V to 240V AC / 8.5 to 7A / 50 to 60Hz
200V to 240V DC / 8.5 to 7A (for CCC only)

+12V max 83A / min 0A (100V to 127V AC)
max 100A / min 0A (200V to 240V AC)
max 100A / min 0A (200V to 240V DC)

12Vsb max 4A / min 0A

Output type 19 pairs gold finger connector

Dimension and Weight

H 437 x W 89 w D 630mm 27.7kg

Accessories Included

1 x Power extension cable, 1 HDD to 2 HDD & 2 FDD, 35 / 25 / 12cm, 22AWG

4 x Mini SAS HD, 12G, INT, 50cm, 30AWG

2 x AC - DC 1200W, titanium level, redundancy, 1U, PMBUS 1.2, +12V / +5Vsb, 360 x 76 x 40mm, HF, RoHS / REACH

24 x Black 3. gen hot-swap 2.5" HDD tray

Accessories Optional



BLUE LINE
IT for Demanding Environments

Blue Line A/S | Kappa 8 | 8382 Hinnerup, Denmark
T +45 8678 5000 | www.blue-line.com

Supermicro Storage Server 2029P-E1CR24H/L

3 x Middle cooling fan 80 x 80 x 38mm, 10.5K RPM for x10
2U ultra & HFT series servers, RoHS / REACH

1 x Supercap module

1 x Mounting PCIe card

1 x HDD Y-split cable

Warranty and After Sales Support

Standard 1 year hardware warranty for barebone

3 year hardware warranty & 1 year cross shipment for
complete system CPU / MEM / DISK

Option for 5 year hardware warranty & 1 year cross
shipment / 3 year hardware warranty & 3 year cross
shipment



BLUE LINE
IT for Demanding Environments

Blue Line A/S | Kappa 8 | 8382 Hinnerup, Denmark
T +45 8678 5000 | www.blue-line.com