

Supermicro Server E300-8D



Highlights

Embedded server for networking applications, security, firewall, and virtualization.



Reduce cost and time spending with our global partner model based on your specific requirements. Let Blue Line take responsibility for delivery on time. Blue Line's ultimate goal is to help our customers get peace of mind by handling all relevant details such as securing the right configuration, software setup, mounting, packaging, labeling etc. Ask for references from your industry.

- Mini chassis
- Intel onboard Xeon D-1518 CPU
- Dual 10G SFP+ & 6 GbE LAN
- AC to DC power adapter
- Option for 1U rackmount kit
- Build-to-order configured to the requirements



BLUE LINE
IT for Demanding Environments

- has more than 30 years experience
- delivers reliable IT solutions for demanding environments
- builds compact and high performance solutions
- focuses on long duration, 24/7-operation, and ruggedness
- is ISO 9001:2015-certified
- is known for providing the best assistance and services in all phases.

Supermicro Server E300-8D

Specifications

Model Type

Server

Form Factor

Mini-1U

Cooling

Passive CPU heat sink & max 3 x 40mm chassis fans

Environment

Operating temperature 0°C to 40°C

Non-operating temperature -40°C to 70°C

Operating humidity 8% to 90% (non-condensing)

Non-operating humidity 5% to 95% (non-condensing)

Processor

CPU Intel® Xeon® D-1518 2.2GHz CPU TDP supports 35W FCBGA 1667

Cores / cache 4 cores / 8 threads / 6MB

Chipset

System on chip

RAM

Memory Capacity 4 x DDR4 DIMM sockets supports up to 128GB DDR4 ECC RDIMM supports up to 64GB DDR4 ECC/non-ECC UDIMM

Memory Type 1600 / 1866 / 2133MHz ECC DDR4 ECC RDIMM & ECC/non-ECC UDIMM

DIMM Sizes 4GB / 8GB / 16GB / 32GB

Memory Voltage 1.2V

Error Detection corrects single-bit errors detects double-bit errors

Storage

1 x Fixed 2.5" drive bay with bracket (when AOC area is not occupied)

Input / Output

Rear 2 x 10G SFP+ LAN, 6 x 1GbE LAN
1 x dedicated IPMI LAN
2 x USB 3.0, 1 x VGA
2 x super DOM power connectors

Internal 4 x SATA3 (6Gbps) ports
1 x TPM 2.0

Expansion

1 x PCI-E 3.0 x8 slots
M.2 interface PCI-E 3.0 x4
Form factor MKey 2242 / 2280 / 22110
Supports SATA devices
Mini PCI-E interface PCI-E 2.0 x1
Supports mSATA

Operating System

WHQL
RHEL / Ubuntu / SUSE

Power Supply

DC power adapter

Dimension and Weight

10" H 43 x W 254 x D 226mm 1.45kg
15" H 276 x W 381 x D 142mm

Accessories Included

1 x 84W DC power adapter

Accessories Optional

RJ45 serial cable for console
4028mm 13K RPM 4pin PWM fan
120W DC power adapter

Warranty and After Sales Support

Standard 1 year hardware warranty for barebone
3 year hardware warranty & 1 year cross shipment for complete system CPU / MEM / DISK
Option for 5 year hardware warranty & 1 year cross shipment / 3 year hardware warranty & 3 year cross shipment



BLUE LINE
IT for Demanding Environments

Blue Line A/S | Kappa 8 | 8382 Hinnerup, Denmark
T +45 8678 5000 | www.blue-line.com