## Supermicro Server 5028A-TN4





## Highlights

Compact design for network security appliance, high performance NAS, and corporate-WINS/DNS/print/login.



Reduce cost and time spending with our global partner model based on your specific requirements. Let Blue Line take responsibility for delivery on time. Blue Line's ultimate goal is to help our customers get peace of mind by handling all relevant details such as securing the right configuration, software setup, mounting, packaging, labeling etc. Ask for references from your industry.

- Space-efficient mini-tower
- Intel onboard Atom C2758 CPU
- 4 x 3.5" and 2 x 2.5" drive bays
- Quad 1GbE
- · Build-to-order configured to the requirements





- has more than 30 years experience
- delivers reliable IT solutions for demanding environments
- builds compact and high performance solutions
  focuses on long duration, 24/7-operation, and ruggedness
- is ISO 9001:2015-certified
- is known for providing the best assistance and services in all phases.

## Supermicro Server 5028A-TN4

## **Specifications**

**Model Type** 

Server

**Form Factor** 

Mini tower

**Environment** 

0°C to 40°C Operating

temperature

Non-operating -20°C to 60°C

temperature

Operating 10% to 85% (non-condensing)

humidity

Non-operating 10% to 95% (non-condensing)

humidity

**Processor** 

Intel® Atom C2758

**RAM** 

Memory 4 x 204-pin DDR3 SO-DIMM slots

Supports up to 64GB DDR3 ECC memory capacity

Memory type 1333 / 1600MHz ECC DDR3 SDRAM 72bit,

204pin gold-plated DIMMs

DIMM sizes 2GB / 4GB / 8GB / 16GB

Memory

1.5V / 1.35V voltage

**Storage** 

4 x Hot-swap 3.5" SATA trays

2 x Internal 2.5" HDD bays

Input / Output

Rear 4 x RJ45 gigabit ethernet, 1 x RJ45

dedicated IPMI

3 x USB 3.0 (2 x rear, 1 x type A) 1 x Fast UART 16550 serial port 1 x SATA DOM power connector

1 x VGA port

Internal 2 x SATA3 (6Gbps) ports, 4 x SATA2 (3Gbps)

1 x TMP 1.2

**Expansion** 

1 x PCI-F 2.0 x8 slot

**Operating System** 

WHQL

RHEL / Ubuntu / SUSE

**Power Supply** 

250W flex ATX multi-output bronze power

supply

AC voltage 100V to 240V / 50 to 60Hz +5V max 14Amp / min 0.5Amp

max 18Amp / min 1Amp (100V to 240V) +12V

-12V max 0.3Amp

+3.3Vmax 12Amp / min 0.3Amp

5VSB max 2.5Amp

**Dimension and Weight** 

H 240 x W 210 x D 279mm 6.8kg

**Accessories Included** 

4 x SATA, INT, round, ST, 21cm, 30AWG

**Accessories Optional** 

Black teac slim DVD-RW SATA drive, HF, RoHS / REACH,

Slim SATA DVD kit

Big 4pin (male) to big 4pin (female) power extension 15cm,

20AWG, RoHS / REACH

**Warranty and After Sales Support** 

Standard 1 year hardware warranty for barebone

3 year hardware warranty & 1 year cross shipment for complete system CPU / MEM / DISK

Option for 5 year hardware warranty & 1 year cross shipment / 3 year hardware warranty & 3 year cross

shipment