


Blue Line Industrial Panel PC-5800



Highlights

Industrial panel pc with extended temperature operation and large range of I/O.

Reduce cost and time spending with our global partner model based on your specific requirements. Let Blue Line take responsibility for delivery on time. Blue Line's ultimate goal is to help our customers get peace of mind by handling all relevant details such as securing the right configuration, software setup, mounting, packaging, labeling etc. Ask for references from your industry.



- Extended temp -20°C to 50°C
- 15.6", 18.5" & 21.5" PCAP multi touch display
- Integrated PC
- UL approved
- Up to full HD resolution 1920 x 1080
- Fanless operation
- Windows 7 / 8 / 10
- Linux support
- IP65 front panel
- VESA / Panel mount
- Other mounting wall / pipe / swivel arm / gas arm



BLUE LINE
IT for Demanding Environments

- has more than 30 years experience
- delivers reliable IT solutions for demanding environments
- builds compact and high performance solutions
- focuses on long duration, 24/7-operation, and ruggedness
- is ISO 9001:2015-certified
- is known for providing the best assistance and services in all phases.

Blue Line Industrial Panel PC-5800

Specifications

Model Type

Panel PC

Construction

Aluminum front bezel and SECC steel chassis

Cooling

Fanless

Ingress Protection

Front IP65

Anti-scratch surface: 7H hardness

Environment

Operating temperature -20°C to +55°C (operation below 0°C demands a storage device with extended temperature)

Storage temperature -30°C to +70°C

Humidity 10% to 95% RH (non-condensing)

Certification

UL, CE, FCC Class A

Display

| | | | |
|-------|------------------------|---------------|---------------|
| 15.6" | 1366 x 768, 16:9, WXGA | TFT LCD panel | LED backlight |
| 18.5" | 1366 x 768, 16:9, WXGA | TFT LCD panel | LED backlight |
| 21.5" | 1920 x 1080, 16:9, FHD | TFT LCD panel | LED backlight |

Touch

Projected capacitive multi touch

Brightness

| | |
|-------|----------|
| 15.6" | 300 nits |
| 18.5" | 300 nits |
| 21.5" | 250 nits |

Colors

Max 16.2M

Viewing Angle

80/80 / 85/85

Processor

Intel Celeron J1900 2.0GHz Quad-core

Chipset

Integrated SoC

RAM

1 x 4GB DDR3L SO-DIMM

Option for 8GB DDR3L SO-DIMM

Storage

2 x 2.5" drive bay (externally accessible)

Option for CFast slot (OEM version)

Rear Input / Output

2 x RS232
2 x RS232/485
1 x USB 3.0
3 x USB 2.0
3 x RJ-45 GbE LAN Intel I210AT controllers
1 x RJ-45 GbE LAN Realtek 8111E controller
1 x DVI-I connector (VGA with adaptor)
2 x SMA antenna holes

Expansion

1 x Mini-PCIe slot (full size)

Operating System

Windows 7 / 8 / 10
Windows Embedded Standard 7 / 8
Windows 10 IoT Enterprise
Ubuntu Linux



BLUE LINE
IT for Demanding Environments

Blue Line A/S | Kappa 8 | 8382 Hinnerup, Denmark
T +45 8678 5000 | www.blue-line.com

Blue Line Industrial Panel PC-5800

Power Supply

+9V to +36V DC-in by terminal block

Power Consumption

| | |
|-------|-------------------------------|
| 15.6" | Max 27.7W (without I/O cards) |
| 18.5" | Max. 25.2W (w/o I/O cards) |
| 21.5" | Max. 29.8W (w/o I/O cards) |

Mounting

Panel mounting
VESA 100

Dimension and Weight

| | | |
|-------|--------------------------|-------|
| 15.6" | H 255 x W 404 x D 49.2mm | 4.6kg |
| 18.5" | H 295 x W 470 x D 49.2mm | 5.7kg |
| 21.5" | H 332 x W 536 x D 48.4mm | 7kg |

Accessories Included

Panel mounting kit

Accessories Optional

12V/5A 60W AC / DC power adapter kit

Warranty and After Sales Support

Standard 1 year (option for 3 years)

Ordering Information

1160



BLUE LINE
IT for Demanding Environments

Blue Line A/S | Kappa 8 | 8382 Hinnerup, Denmark
T +45 8678 5000 | www.blue-line.com