## Mobile Operator Station T500



## Highlights

Blue Line's Mobile Operator Station T500 is designed for life science environments that require a configurable and light weight solution but also want the benefit of a powered mobile workstation. Cleanable with IPA wipe down and damp cloth.

Equip with one or two HMI/monitors, client, keyboard/mouse, scanner etc. and achieve greater productivity with Blue Line Mobile Workstation technology. Integrated battery with high 500Wh capacity for continuous productivity.

Best in class ergonomics and user satisfaction due to the stepless electric height adjustment via actuator supporting both seated and standing operation. Hygienic casters make it easy to move around as needed, always ready for use when needed.

Let us configure your mobile operation station according to your requirements.

Blue Line's modular design makes it possible to configure to specific needs in functionality, finish and environment. Get free advice from our experts and let us set up a Teams meeting for an online demo and Q&A. Benefit from our experience and knowledge based on numerous installations in biotech and pharmaceutical sites around the world.

- Mobile IT operation in life science environments
- Equipable with one or two HMI/monitors, client, keyboard/mouse, scanner etc.
- Electric height adjustment via actuator for both seated and standing operation
- Room for client and other equipment
- Powered by 100-240V AC or integrated battery with a capacity of 500Wh
- Display for battery power status
- Charge the battery by plugging in the 100-240V AC
- Hygienic casters
- Configuration according to your requirements







- has more than 30 years experience
- delivers reliable IT solutions for demanding environments
- builds compact and high performance solutions
  focuses on long duration, 24/7-operation, and ruggedness
- is ISO 9001:2015-certified
- is known for providing the best assistance and services in all phases.

## Mobile Operator Station T500

## **Specifications**

**Model Type** 

Mobile Operator Station

Construction

Compact laminate

**Cleaning** 

Wipe down cleaning IPA 70% and damp cloth

**Casters** 

4 casters, 2 with brakes

Cooling

**Fanless** 

**Ingress Protection** 

IP20

**Environment** 

Operating 0°C to +40°C

temperature

Storage -20°C to +60°C

temperature

Humidity 10 to 90% @ 40°C (non-condensing)

Certification

CE

НМІ

Equipable with one or two monitors

**PC/Client** 

Placed in the mobile operator station's compartment

I/O

Customisable depending on client configuration

USB

GbE LAN

Video Interface

**Work Surface** 

Polyrey laminate

**Height adjustment** 

Fixed height or electric adjustable (table height 83 to 120cm)

Power

The trolley is powered either by 100-240V AC or the integrated battery

The integrated battery has a capacity of 500Wh

Battery status indicator - LCD display with remaining battery time

**Accessories Included** 

Bracket for single screen

Power cable

**Accessories Optional** 

Option for dual screen bracket

**Dimension and Weight** 

H 123 x W 58 x D 62cm

Weight 42kg without monitor and thin client

**Warranty and After Sales Support** 

Standard 1 year (optional 3 years)