



- has more than 30 years experience
 delivers reliable IT solutions for demanding environments
 builds compact and high performance solutions
 focuses on long duration, 24/7-operation, and ruggedness
 is ISO 9001:2015-certified
- is known for providing the best assistance and services in all phases.

Highlights

A waterproof stainless steel IP69K Monitor developed for demanding food and beverage production. Withstands intensive spray down and high pressure cleaning over and over again. The fully sealed enclosure is IP66 dust and waterproof as well as IP69K high pressure proof that exceeds NEMA 4X rating enabling the market's fastest and most complete cleaning.

Designed for 24/7 operation, with low power consumption, passive cooling and without moving parts for maximum operational reliability. Screen sizes in 15.6" or 21.5" with auto-calibrated touch technology for seamless operation, even with gloves.

The rear side of the IP69K Monitor supports tube and swingarm mounting with internal cable wiring providing the market's best long term protection against high pressure water treatment.

Benefit from our experience from numerous installations around the world. Let us prepare a proposal that ensures the best functionality, ergonomics and occupies as little space as possible, such as integration with food processing equipment.

Reduce cost and time spending with our global partner model based on your specific requirements. Let Blue Line take responsibility for delivery on time. Blue Line's ultimate goal is to help our customers get peace of mind by handling all relevant details such as securing the right configuration, software setup, mounting, packaging, labeling etc. Ask for references from your industry.

- Food / wet environment
- IP69K high pressure waterproof Monitor
- Stainless steel AISI 316L
- 15.6" or 21.5" PCAP multi touch display

IT for Demanding Environments

- Full HD resolution 1920 x 1080
- Touch on/off button on the side
- Fanless operation
- Optional tube mount and swivel arm with hidden connectors and cables







has more than 30 years experience.

- · delivers reliable IT solutions for demanding environments
- builds compact and high performance solutions
 focuses on long duration, 24/7-operation, and ruggedness
- is ISO 9001:2015-certified
- is known for providing the best assistance and services in all phases.

Specifications

| Model Type HMI stainless steel Monitor | | Colors 16.7M | |
|--|--|--|--|
| Construction Fully sealed enclosure in acid resistant stainless steel AISI 316L | | Viewing Angle 160/160 - 178/178 | |
| Cooling Fanless | | Rear Input / Output 1 x HDMI (IP68) 1 x 3pin DC power (IP68) 1 - USD to a th (IP60) | |
| Ingress Protection IP66/69K high pressure proof | | 1 x USB-touch (IP68) 1 x M4 ground screw All connectors come with waterproof cap | |
| Environment Operating 0°C to +50°C temperature (For 15.6" option for -20°C to +60°C) | | Power Supply +9V to +36V DC-input | |
| Storage temperatu Humidity | -30°C to +70°C | Power Consumption Max 35W | |
| Certification CE / FCC CLASS A | | Mounting VESA 100 (I/O ports in center) Stainless steel supporting arm | |
| Display 15.6" 21.5" | 1920 x 1080, 16:9, FHD color TFT LCD 1920 x 1080, 16:9, FHD color TFT LCD | Stainless steel tube mount Dimension and Weight | |
| Touch | | 15.6"H 290 x W 440 x D 55mm6.5kg21.5"H 362 x W 571 x D 55mm9.5kg | |
| Projected capacitive multi touch (supports gloves) Anti Shatter Film for projected capacitive multi touch (optional) Resistive touch (optional) | | Special Function Touch on/off button on the side edge for hygienic cleaning | |
| No touch (optional) Optical bonding (optional) | | Accessories Included AC to DC power adapter with M12 | |
| Brightness 15.6" 21.5" | 300 nits 300 nits | Accessories Optional | |
| All sizes | Option for high brightness 1000 nits | USB cable, HDMI cable, Power cable Stainless steel scanner bracket | |



Ξ

IT for Demanding Environments

LINE

Warranty and After Sales Support Standard 1 year (option for 3 years)

Ordering Information

512



Blue Line A/S | Kappa 8 | 8382 Hinnerup, Denmark T +45 8678 5000 | www.blue-line.com