Blue Line IPC-8000 Power Mini



Highlights

Compact industrial pc supports full length/height PCI and PCIe cards. Benefit from high performance Intel 11th generation processors. Blue Line IPC-8000 Power Mini supports high performance GPU for Al/inference.

Reduce cost and time spending with our global partner model based on your specific requirements. Let Blue Line take responsibility for delivery on time. Blue Line's ultimate goal is to help our customers get peace of mind by handling all relevant details such as securing the right configuration, software setup, mounting, packaging, labeling etc. Ask for references from your industry.

- Fast & flexible industrial pc
- Intel 11th generation core processor
- Windows 10 / 11 / Linux
- 2 x USB 3.2, 1 x USB 3.2 Gen2 type C, 2 x 2.5GbE
- Optional 4 x COM, 8 x USB, DIO
- Long product life cycle
- Compact chassis
- Build-to-order configured to your requirements



- has more than 30 years experience
- delivers reliable IT solutions for demanding environments
- builds compact and high performance solutions
 focuses on long duration, 24/7-operation, and ruggedness
- is ISO 9001:2015-certified
- is known for providing the best assistance and services in all phases.

Blue Line IPC-8000 Power Mini

Specifications

Model Type

Compact PC

Form Factor

Compact chassis

Construction

Heavy duty cold rolled steel

Cooling

One 80 x 80 x 25mm system front fan, with dustfilter

Option for $80 \times 80 \times 25$ mm low noise fan Option for $80 \times 80 \times 25$ mm high speed fan

Certification

CE

Processor

Intel Core 11th gen. i3 / i5 / i7 / i9

Pentium G Series Celeron G Series

Chipset

Intel Q470

Integrated Intel UHD Graphics 750/710, supports OpenGL 4.5 and DirextX 12.1 $\,$

Intel PTT (TPM 2.0)

Watchdog Timer Software Programmable supports 1 to 255 sec. System reset

RAM

4 x 288-Pin DDR4 2933MHz UDIMM, supports up to 128GB

Storage

1 x 5.25" / 1 x 3.5" drive bay (Option for internal 2.5" / 3.5" drives)

Front Input / Output

Option for 2 x USB 3.2 Gen 1 via internal header

Rear Input / Output

Rear 1 x HDMI 1.4b (up to 4096 x 2160@30Hz)

2 x RJ45 LAN: Intel I225-V 2.5GbE

controller

2 x USB 3.2 Gen1 (5Gb/s) Type A 1 x USB 3.2 Gen2 (10Gb/s) Type C

Option 2 x RS-232 / 2 x RS-422/485 (via pin

header)

10 x USB 2.0 (6 x pin header, 4 x

backplane pin header)

7.1 channel HD Audio kit with Realtek

ALC888S

1 x 12-bit digital I/O (2x7 pin)

Internal 4 x SATA 6GB/s (RAID 0/1/5/10 supported)

Expansion

Passive backplane with 5 available

kplane PCle 3.0 (x4 Lanes slot) h 5

slots PICMG 1.3 CPU Card

1 x M.2 A Key (2230) w/PCle x2/USB 2.0 1 x M.2 M Key (2280/2242) w/PCle x4/SATA 1 x M.2 B Key (3042/3052/2242/2280)

3 x PCI, 1 x PCIe 3.0 (x16 Lanes slot), 1x

w/PCle x2/USB 2.0

Operating System

Windows 10 / 11

Windows 10 IoT Enterprise

Linux

Power Supply

Industrial PSU 650W ATX 12V v2,3, 80mm double ball bearing FAN, Full Range AC input, 80 PLUS Gold

IEC 62368-1 compliant

ErP Lot 6 2013 compliant

EMI/EMC: CE Class B and FCC Class B, RCM Safety: cTUVus , TUV, CB, CCC, BSMI, RCM (SAA) Option for 350W, 750W, 850W & 1000W PSU

Option for 500W redundant PSU

Power Consumption

TBD

Dimension and Weight

H 181 x W 232 (273 w/mounting bracket) x D 400mm



Blue Line IPC-8000 Power Mini

Mounting

Wall mounting

Accessories Included

Wall mounting bracket

PCI/PCIe card hold down retention bar

Accessories Optional

7.1 channel HD audio kit with Realtek ALC888S (1 x Line in,

1 x Line out, 1 x Mic and 1 x Center/Sub)

1 x 2.5" Rugged Hot-swap w/Thumbscrews and key lock in 3.5" bay $\,$

2 x 2.5" Trayless Hot-swap w/key lock in 3.5" bay

4 x 2.5" Trayless Hot-swap w/key lock in 5.25" bay

Warranty and After Sales Support

Standard 1 year (option for 3 years)

Ordering Information

2205-5